

View Online at https://aerobasegroup.com/nsn/5905-01-261-4626

## Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

-30.0/+30.0

#### **Electrical Resistance:**

4.990 kilohms

## **Resistance Tolerance In Percent:**

-1.000/+1.000

#### Ambient Tempurature In Deg Celsius At Full Rated Power:

#### 25.0

## Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

275.0

## Tempurature Range Of Tempurature Coefficient In Deg Celsius:

-55.0/+275.0

#### **Inclosure Method:**

Encased

#### **Terminal Type:**

Tab, solder lug

# Reliability Indicator:

\_ . . . . . .

# Established

**Reliability Failure Rate Level In Percent:** 

0.010

#### **Terminal Length:**

0.266 inches

#### Body Length:

0.600 inches

#### Body Width:

0.334 inches

#### **Body Height:**

0.320 inches

## Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

0.444 inches

#### **Power Dissipation Rating In Watts:**

3.000 free air

#### **Terminal Width:**

0.085 inches

#### Mounting Hole Size:

0.093 inches

#### Cubic Measure (non-core):

0.064 cubic inches

## Unpackaged Unit Weight:

3.0 grams

## Style Designator:

Axial terminal (s)



## Test Data Document:

81349-mil-r-39009 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## Specification Data:

81349-mil-r-39009/1 government specification

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A001a0