## NSN 5905-01-262-0713

Film Fixed Resistor - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5905-01-262-0713  |
|--|
| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:  |
| -5.0/+5.0 first temp coefficient   |
| Electrical Resistance:   |
| 500.000 ohms   |
| Resistance Tolerance In Percent:   |
| -0.005/+0.005  |
| Ambient Tempurature In Deg Celsius At Full Rated Power:  |
| 125.0  |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  |
| 175.0  |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius:   |
| -55.0/+125.0 temp range of first temp coefficient  |
| Inclosure Method:  |
| Encapsulated   |
| Terminal Type:   |
| Wire lead  |
| Mil-std-1276 Wire Lead Type Designator:  |
| C  |
| Reliability Indicator:   |
| Established  |
| Reliability Failure Rate Level In Percent:   |
| 0.010  |
| Terminal Length:   |
| 1.375 inches   |
| Body Length:   |
| 0.310 inches   |
| Body Width:  |
| 0.375 inches   |
| Body Height:   |
| 0.110 inches   |
| Power Dissipation Rating In Watts:   |
| 0.300 free air   |
| Cubic Measure (non-core):  |
| 0.011 cubic inches   |
| Unpackaged Unit Weight:  |
| 1.000 grams  |
| Style Designator:  |
| Terminals one edge   |
| Test Data Document:  |
| 81349-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |

format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Specification Data:**

81349-mil-r-55182/9 government specification

## NSN 5905-01-262-0713

Film Fixed Resistor - Page 2 of 2



| _ |   |    | • |    |    |
|---|---|----|---|----|----|
| • | n | ο. | • | 18 | e: |
|   |   |    |   |    |    |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A001a0