## NSN 5905-01-262-6708

N/a

Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-262-6708

| Electrical Resistance:   |
|--|
| 2.200 kilohms each resistor  |
| Resistance Tolerance In Percent:   |
| -2.000/+2.000 each resistor  |
| Ambient Tempurature In Deg Celsius At Full Rated Power:  |
| 70.0   |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  |
| 125.0  |
| Inclosure Method:  |
| Encapsulated   |
| Terminal Quantity:   |
| 8  |
| Terminal Type:   |
| Pin  |
| Reliability Indicator:   |
| Not established  |
| Terminal Length:   |
| 0.135 inches   |
| Body Length:   |
| 0.783 inches   |
| Body Width:  |
| 0.074 inches   |
| Body Height:   |
| 0.187 inches   |
| Schematic Diagram Designator:  |
| Isolated array   |
| Power Dissipation Rating In Watts:   |
| 1.500 total network  |
| Terminal Width:  |
| 0.049 inches   |
| Identical Value Resistor Quantity:   |
| 4 each resistor  |
| Unpackaged Unit Weight:  |
| 1.5 grams  |
| Style Designator:  |
| Single inline  |
| Test Data Document:  |
| 81349-mil-prf-83401 specification specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in |
| specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on      |
| certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).                      |
| Specification Data:  |
| 81349-mil-prf-83401/8 government specification government specification  |
| Shelf Life:  |

## NSN 5905-01-262-6708

Film Fixed Resistor Network - Page 2 of 2



|    | • - |      |         |   |
|----|-----|------|---------|---|
| In | ıŧ  | ( )t | Measure | • |
|    |     |      |         |   |

--

Demilitarization:

No

Fiig:

A001a0

Mil-std (military Standard):

Mil-prf-83401 spec.