NSN 5905-01-262-6719

Precision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-262-6719 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** Between 1.296 inches and 1.328 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.500 inches **Mounting Bushing Length:** Between 0.234 inches and 0.266 inches **Body Length:** Between 0.620 inches and 0.630 inches **Shaft Style:** Round **Shaft Bearing Type:** Ball **Actuator Type:** Single shaft **Maximum Starting Torque:** 0.70 inch-ounces **Maximum Running Torque:** 0.50 inch-ounces **Shaft Runout:** 0.001 inches **Lateral Runout:** 0.002 inches **Pilot Diameter Runout:** 0.0015 inches **Shaft Radial Play:** 0.002 inches **Mounting Method:** Locking bushing w/panel seal **Electrical Resistance Per Section:** 10.000 kilohms single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-150.0/+300.0 single section

NSN 5905-01-262-6719

Precision Nonwire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating	Per	Section	In	Watts:
2.0 free air single section				

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0