## NSN 5905-01-263-2761

Precision Nonwire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-01-263-2761 **Section Quantity: Body Style:** Cylindrical hole/slot mounted **Reliability Indicator:** Not established **Body Diameter:** 0.937 inches **Shaft Diameter:** Between 0.1245 inches and 0.1247 inches **Shaft Length:** 0.420 inches **Body Length:** 0.450 inches **Mounting Hole/stud Circle Diameter:** 0.400 inches **Shaft Style:** Round **Shaft Bearing Type:** Bearing **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 330.0 **Maximum Starting Torque:** 0.27 inch-ounces **Maximum Running Torque:** 0.27 inch-ounces **Nonturn Device Location:** At 12 oclock **Nonturn Device Radius:** Between 0.135 inches and 0.140 inches **Shaft End Play:** 0.005 inches **Shaft Runout:** 

0.001 inches **Lateral Runout:** 0.001 inches **Shaft Radial Play:** 0.001 inches **Fragility Factor:** Moderately rugged

## NSN 5905-01-263-2761

N/a

Precision Nonwire Wound Variable Resistor - Page 2 of 3



End Application:
B-1b aircraft
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Mounting Facility Quantity:
4
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Threaded hole
Features Provided:
Humidity proof
Cubic Measure:
0.310 cubic inches
Electrical Resistance Per Section:
6.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
Between 324.0 and 326.0
Function Conformity Tolerance Per Section:
-0.15/+0.15 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Power Dissipation Rating Per Section In Watts:
0.1 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-2.0/+2.0 single section
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
71.0 single section
Special Features:
Terminal wire leads 12 in. Long
Terminal Type And Quantity:
3 wire lead
Shelf Life:
N/a

## NSN 5905-01-263-2761

Precision Nonwire Wound Variable Resistor - Page 3 of 3



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A002a0