NSN 5905-01-263-4914

Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-263-4914

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: -20.0/+20.0 Electrical Resistance: 37.400 ohms Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reactance Characteristic: Inductive Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.312 inches Body Length: 0.875 inches
Electrical Resistance: 37.400 ohms Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reactance Characteristic: Inductive Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.312 inches Body Length:
Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reactance Characteristic: Inductive Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.312 inches Body Length:
Resistance Tolerance In Percent: -1,000/+1,000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reactance Characteristic: Inductive Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.312 inches Body Length:
-1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reactance Characteristic: Inductive Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.312 inches Body Length:
Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reactance Characteristic: Inductive Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.312 inches Body Length:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reactance Characteristic: Inductive Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.312 inches Body Length:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reactance Characteristic: Inductive Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.312 inches Body Length:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reactance Characteristic: Inductive Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.312 inches Body Length:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reactance Characteristic: Inductive Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.312 inches Body Length:
-55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reactance Characteristic: Inductive Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.312 inches Body Length:
Inclosure Method: Encapsulated Terminal Type: Wire lead Reactance Characteristic: Inductive Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.312 inches Body Length:
Encapsulated Terminal Type: Wire lead Reactance Characteristic: Inductive Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.312 inches Body Length:
Terminal Type: Wire lead Reactance Characteristic: Inductive Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.312 inches Body Length:
Wire lead Reactance Characteristic: Inductive Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.312 inches Body Length:
Reactance Characteristic: Inductive Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.312 inches Body Length:
Inductive Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.312 inches Body Length:
Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.312 inches Body Length:
Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.312 inches Body Length:
Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.312 inches Body Length:
0.001 Terminal Length: 1.500 inches Body Diameter: 0.312 inches Body Length:
Terminal Length: 1.500 inches Body Diameter: 0.312 inches Body Length:
1.500 inches Body Diameter: 0.312 inches Body Length:
Body Diameter: 0.312 inches Body Length:
0.312 inches Body Length:
Body Length:
0.875 inches
Power Dissipation Rating In Watts:
5.000 free air
Cubic Measure (non-core):
0.085 cubic inches
Unpackaged Unit Weight:
5.0 grams
Style Designator:
Axial terminal each end
Test Data Document:
81349-mil-r-39007 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-r-39007/6 government specification

N/a

Shelf Life:

NSN 5905-01-263-4914

Wire Wound Fixed Resistor - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A001a0