

View Online at <https://aerobasegroup.com/nsn/5905-01-263-5839>

**Section Quantity:**

1

**Body Style:**

Cylindrical bushing mounted

**Reliability Indicator:**

Not established

**Body Diameter:**

Between 0.860 inches and 0.890 inches

**Shaft Diameter:**

Between 0.2494 inches and 0.2497 inches

**Shaft Length:**

Between 0.781 inches and 0.843 inches

**Mounting Bushing Length:**

Between 0.297 inches and 0.327 inches

**Body Length:**

Between 0.735 inches and 0.765 inches

**Shaft Style:**

Round, slotted

**Shaft Bearing Type:**

Sleeve

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

Between 1080.0 and 1090.0

**Nonturn Device Location:**

At 12 oclock

**Nonturn Device Radius:**

0.290 inches

**Shaft End Play:**

0.010 inches

**Shaft Runout:**

0.003 inches

**Lateral Runout:**

0.005 inches

**Pilot Diameter Runout:**

0.003 inches

**Shaft Radial Play:**

0.003 inches

**Fragility Factor:**

Moderately rugged

**Screw Thread Diameter:**

0.375 inches

**Screw Thread Series Designator:**

Unef

**Screw Thread Qty Per Inch (tpi):**

32.0

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Standard bushing

**Features Provided:**

Humidity proof

**Cubic Measure:**

0.606 cubic inches

**Electrical Resistance Per Section:**

100.0 ohms single section

**Rotary Actuator Travel In Angular Deg:**

Between 1080.0 and 1090.0

**Function Conformity Tolerance Per Section:**

-0.25/+0.25 single section

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

125.0 single section

**Power Dissipation Rating Per Section In Watts:**

1.0 free air single section

**Function Conformity Per Section:**

Single section independent linearity

**Resistance Tolerance Per Section In Percent:**

-5.0/+5.0 single section

**Actuator Travel Control Feature:**

Stops

**Function Characteristic Per Section:**

Single section linear

**Temperature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:**

-20.0/+20.0 single section

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

70.0 single section

**Precious Material And Location:**

Terminal surfaces gold

**Precious Material:**

Gold

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A002a0