## NSN 5905-01-265-7304

Film Fixed Resistor - Page 1 of 2

-25.0/+25.0

600.000 kilohms

**Electrical Resistance:** 

**Resistance Tolerance In Percent:** 



View Online at https://aerobasegroup.com/nsn/5905-01-265-7304

**Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:** 

| -0.100/+0.100  |
|--|
| Ambient Tempurature In Deg Celsius At Full Rated Power:  |
| 125.0  |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  |
| 175.0  |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius:   |
| -55.0/+175.0   |
| Inclosure Method:  |
| Encapsulated   |
| Terminal Type:   |
| Wire lead  |
| Reliability Indicator:   |
| Established  |
| Reliability Failure Rate Level In Percent:   |
| 0.001  |
| Terminal Length:   |
| 1.500 inches   |
| Body Diameter:   |
| 0.250 inches   |
| Body Length:   |
| 0.750 inches   |
| Power Dissipation Rating In Watts:   |
| 0.500 free air   |
| Unpackaged Unit Weight:  |
| 1.600 grams  |
| Style Designator:  |
| Axial terminal each end  |
| Test Data Document:  |
| 81349-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain          |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).                            |
| Specification Data:  |
| 81349-mil-r-55182/6 government specification   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
| Demilitarization:  |
| No   |

## NSN 5905-01-265-7304

Film Fixed Resistor - Page 2 of 2



Fiig:

A001a0