NSN 5905-01-265-8094

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-265-8094 **Section Quantity:** 3 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 0.9688 inches Pilot Length: 0.0500 inches **Undercut Width:** 0.0500 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 1.650 inches **Body Length:** 0.667 inches **Mounting Lip Depth:** 0.0620 inches **Shaft Style:** Round **Shaft Bearing Type:** Ball **Actuator Type:** Single shaft **Nonturn Device Location:** At 3 oclock **Fragility Factor:** Moderately rugged **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Clamp ring **Features Provided:** Humidity proof **Cubic Measure:**

0.491 cubic inchesElectrical Resistance Per Section:5.0 kilohms all sectionsFixed Tap Quantity Per Section:

1 all sections

NSN 5905-01-265-8094

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Actuator Travel Control Feature:
Stops
Standard Taper Curve Per Section:
A all sections
Terminal Type And Quantity:
4 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0