Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-265-9471

## Section Quantity:

2

Body Style:

Cylindrical bushing mounted

## **Reliability Indicator:**

Not established

### **Body Diameter:**

1.094 inches

### Shaft Diameter:

0.250 inches

Shaft Length:

0.625 inches

### Mounting Bushing Length:

0.500 inches

### Body Length:

### 1.266 inches

Shaft Style:

Round, slotted

### Actuator Type:

Single shaft

### Effective Electrical Rotation In Deg Angular Rotation:

Between 309.0 and 320.0

## Nonturn Device Location:

At 9 oclock

## Nonturn Device Radius:

0.531 inches

### Screw Thread Diameter:

0.375 inches

### Screw Thread Series Designator:

Unef

## Screw Thready Qty Per Inch (tpi):

32.0

## **Terminal Location:**

Radially positioned over less than half the circumference

## **Mounting Method:**

Locking bushing

## **Electrical Resistance Per Section:**

2.0 megohms all sections

## Rotary Actuator Travel In Angular Deg:

Between 309.0 and 320.0

# Resistance Tempurature Characteristic Range Per Section In Percent:

-3.0/+0.0 -55 degrees celsius all sections and -5.0/+10.0 -25 degrees celsius all sections and -5.0/+10.0 25 degrees celsius all sections and

+0.0/+3.0 120 degrees celsius all sections



### Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 all sections

## Power Dissipation Rating Per Section In Watts:

2.0 free air all sections

**Resistance Tolerance Per Section In Percent:** 

-10.0/+10.0 all sections

**Actuator Travel Control Feature:** 

Stops

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 all sections

**Standard Taper Curve Per Section:** 

A all sections

#### **Test Data Document:**

81349-mil-r-94 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### **Terminal Type And Quantity:**

6 tab, solder lug

#### **Specification Data:**

81349-mil-r-94/6 government specification

Shelf Life:

N/a

Unit Of Measure:

--

### **Demilitarization:**

No

Fiig:

A002a0