NSN 5905-01-266-5351

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-266-5351 **Section Quantity: Body Style:** Rectangular **Reliability Indicator:** Not established **Terminal Length:** 0.200 inches **Shaft Diameter:** Between 0.075 inches and 0.085 inches **Shaft Length:** Between 0.050 inches and 0.070 inches **Body Length:** Between 0.360 inches and 0.390 inches **Body Width:** Between 0.360 inches and 0.390 inches **Body Height:** 0.200 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 7200.0 **Maximum Starting Torque:** 5.00 inch-ounces **Maximum Running Torque:** 5.00 inch-ounces **Center To Center Distance Between Terminals:** 2.000 inches **Terminal Location:** Right adjacent side two rows **Mounting Method: Terminal Center To Center Distance Between Terminal Rows:** 1.000 inches **Electrical Resistance Per Section:** 5.0 kilohms single section **Rotary Actuator Travel In Angular Deg:**

Center To Center Distance Between Center Terminal And Outside Terminal:

1.000 inches

NSN 5905-01-266-5351

Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 150.0 single section **Power Dissipation Rating Per Section In Watts:** 0.5 free air single section **Resistance Tolerance Per Section In Percent:** -10.0/+10.0 single section **Actuator Travel Control Feature:** Clutch Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 85.0 single section **Terminal Type And Quantity:** 3 pin Shelf Life: N/a **Unit Of Measure: Demilitarization:** No