## NSN 5905-01-266-7717

Film Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-266-7717

Electrical Resistance: 115.000 ohms Resistance Tolerance In Percent: -1.000 to 1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -65.0 to 125.0 Inclosure Method: Uninclosed Terminal Type: Terminal Type: Established Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Body Length: 0.050 inches Body Width: 0.050 inches Body Height: Between 0.010 inches and 0.040 inches Power Dissipation Rating In Watts: 0.100 frea air Unipackaged Unit Weight: 0.000 rame Style Designator: Terminaling-55342 specification (includes engineering type bulleins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mit-553424 government specification Na Unit Of Measure:	Tompurature Coefficient Of Registeres In Dam Box Dog Coloius
Electrical Resistance: 115.000 ohms Resistance Tolerance In Percent: -1.000 to 1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -85.0 to 125.0 Inclosure Method: Uninclosed Terminal Type: Terminal type per body style Reliability Indicator: Established Reliability Indicator: Body Length: 0.050 inches Body Length: 0.050 inches Body Wildth: 0.150 inches Body Wildth: 0.150 inches Body Wildth: 0.150 inches Body Wildth: 0.150 inches Body Height: Between 0.010 inches and 0.040 inches Power Dissipation Rating in Watts: 0.000 free air Unpackaged Unit Weight: 0.0000 frems Style Designator: Termination pad each end Test Data Document: 81349-mil+-755342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data: 81349-mil+-755342/d government specification Sheff Life: N/a	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
115.000 ohms Resistance Tolerance In Percent: -1.000 to 1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0 to 125.0 Inclosure Method: Uninclosed Terminal Type: Terminal type per body style Reliability Indicator: Established Reliability Indicator: Established Reliability Fallure Rate Level In Percent: 0.010 Body Langth: 0.050 inches Body Wildth: 0.150 inches Body Wildth: 0.150 inches Body Height: Between 0.010 inches and 0.040 inches Power Dissipation Rating In Watts: 0.100 free air Unpackaged Unit Weight: 0.0001 grams Style Designator: Terminality pad each end Test Data Document: 81349-milt-755342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.) Specification Data: 81349-milt-755342/ government specification Sheff Life: N/a	
Resistance Tolerance In Percent: -1.000 to 1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 7.0.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0 to 125.0 Inclosure Method: Uninclosed Terminal Type: Terminal Type: Terminal Type body style Reliability Indicator: Established Reliability Faiture Rate Level In Percent: 0.010 Body Length: 0.050 inches Body Width: 0.150 inches Body Width: 0.150 inches Body Height: Between 0.010 inches and 0.040 inches Power Dissipation Rating In Watts: 0.100 free air Unpackaged Unit Weight: Unpackaged Unit Weight: Terminal top pet each end Test Data Document: 814349-mil-75542 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as 'typical', 'average', '', etc.). Specification Data: 814349-mil-7553424 government specification Sheff Life: No	
-1.000 to 1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -85.0 to 125.0 Inclosure Method: Uninclosed Terminal Type: Terminal type per body style Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Body Length: 0.050 inches Body Width: 0.150 inches Body Width: 0.150 inches Body Width: 0.150 inches Body Begiand Unit Weight: 0.000 ing rams Style Designator: Terminal top Begiandor: Terminal top Begiandor: 1 Termination pad each end Test Data Document: 81349-mill-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data: 814349-mill-55342/4 government specification Shelf Life: No	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0 to 125.0 Inclosure Method: Uninclosed Terminal Type: Terminal Type: Terminal type per body style Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Body Length: 0.050 inches Body Width: 0.150 inches Body Width: 0.150 inches Body Height: Between 0.010 inches and 0.040 inches Power Dissipation Rating In Watts: 0.100 free air Unpackaged Unit Weight: 0.0001 grams Style Designator: Termination pad each end Test Data Document: 81349-mill-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data: 81849-mill-553424 government specification Shelf Life: N/a	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -85.0 to 125.0 Inclosure Method: Uninclosed Terminal Type: Terminal Type: Terminal Type: Betablish Indicator: Betablish Indicator: Betablish Red Reliability Indicator: Betablished Reliability Failure Rate Level In Percent: 0.010 Body Length: 0.050 inches Body Width: 0.150 inches Body Width: 0.150 inches Body Height: Between 0.010 inches and 0.040 inches Power Dissipation Rating In Watts: 0.100 free air Unpackaged Unit Weight: 0.0001 grams Style Designator: Termination pad each end Test Data Document: 81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.) Specification Data: 81349-mil-r-553424 government specification Shelf Life: N/a	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  125.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0 to 125.0  Inclosure Method: Uninclosed  Terminal Type:  Terminal Type:  Terminal type per body style  Reliability Indicator: Established  Reliability Failure Rate Level In Percent: 0.010  Body Length: 0.050 inches  Body Width: 0.150 inches  Body Height: Between 0.010 inches and 0.040 inches  Power Dissipation Rating In Watts: 0.100 free air  Unpackaged Unit Weight: 0.00001 grams  Style Designator: Termination pad each end  Test Data Document:  81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81349-mil-r-55342/4 government specification  Shelf Life:  N/a	
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0 to 125.0 Inclosure Method: Uninclosed Terminal Type: Terminal type per body style Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Body Length: 0.050 inches Body Width: 0.150 inches Body Width: 0.150 inches Body Height: Between 0.010 inches and 0.040 inches Power Dissipation Rating In Watts: 0.100 free air Unpackaged Unit Weight: 0.0001 grams Style Designator: Termination pad each end Test Data Document: 81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-55342/4 government specification Shelf Life: N/a	
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0 to 125.0 Inclosure Method: Uninclosed Terminal Type: Terminal Type: Terminal type per body style Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Body Length: 0.050 inches Body Width: 0.150 inches Body Width: 0.150 inches Body Height: Between 0.010 inches and 0.040 inches Power Dissipation Rating In Watts: 0.100 free air Unpackaged Unit Weight: 0.0001 grams Style Designator: Termination pad each end Test Data Document: 81349-milt-r55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data: 81349-milt-r553424 government specification Shelf Life: N/a	
Inclosure Method: Uninclosed Terminal Type: Terminal Type: Terminal type per body style Reliability Indicator: Established Reliability Faiture Rate Level In Percent: 0.010 Body Length: 0.050 inches Body Width: 0.150 inches Body Width: 0.150 inches Body Height: Between 0.010 inches and 0.040 inches Power Dissipation Rating In Watts: 0.100 fee air Unpackaged Unit Weight: 0.100001 grams Style Designator: Termination pad each end Test Data Document: 81349-milr-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-milr-553424 government specification Shelf Life: N/a	
Inclosure Method: Uninclosed Terminal Type: Terminal type per body style Reliability Indicator: Established Reliability Failure Rate Level in Percent: 0.010 Body Length: 0.050 inches Body Width: 0.150 inches Body Width: 0.150 inches Body Height: Between 0.010 inches and 0.040 inches Power Dissipation Rating in Watts: 0.100 free air Unpackaged Unit Weight: 0.0001 grams Style Designator: Termination pad each end Test Data Document: 81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-55342/4 government specification Shelf Life: N/a	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Uninclosed Terminal Type: Terminal type per body style Reliability Indicator: Established Reliability Failure Rate Level in Percent: 0.010 Body Length: 0.050 inches Body Width: 0.150 inches Body Wight: Between 0.010 inches and 0.040 inches Power Dissipation Rating in Watts: 0.100 free air Unpackaged Unit Weight: 0.0001 grams Style Designator: Termination pad each end Test Data Document: 81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-55342/4 government specification Shelf Life: N/a	-65.0 to 125.0
Terminal type per body style Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Body Length: 0.050 inches Body Width: 0.150 inches Body Height: Between 0.010 inches and 0.040 inches Power Dissipation Rating In Watts: 0.100 free air Unpackaged Unit Weight: 0.0001 igrams Style Designator: Termination pad each end Test Data Document: B1349-milr-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-1-55342/4 government specification Shelf Life: N/a	Inclosure Method:
Terminal type per body style  Reliability Indicator:  Established  Reliability Failure Rate Level In Percent:  0.010  Body Length: 0.050 inches  Body Width: 0.150 inches  Body Height:  Between 0.010 inches and 0.040 inches  Power Dissipation Rating In Watts: 0.100 free air  Unpackaged Unit Weight: 0.0001 grams  Style Designator:  Termination pad each end  Test Data Document:  81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81349-mil-r-55342/4 government specification  Shelf Life:  N/a	Uninclosed
Reliability Indicator: Established  Reliability Failure Rate Level In Percent:  0.010  Body Length: 0.050 inches  Body Width: 0.150 inches  Body Height: Between 0.010 inches and 0.040 inches  Power Dissipation Rating In Watts: 0.100 free air  Unpackaged Unit Weight: 0.0001 grams  Style Designator: Termination pad each end  Test Data Document:  81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81349-mil-r-55342/4 government specification  Shelf Life: N/a	Terminal Type:
Established  Reliability Failure Rate Level In Percent:  0.010  Body Length:  0.050 inches  Body Width:  0.150 inches  Body Height:  Between 0.010 inches and 0.040 inches  Power Dissipation Rating In Watts:  0.100 free air  Unpackaged Unit Weight:  0.0001 grams  Style Designator:  Termination pad each end  Test Data Document:  81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81349-mil-r-55342/4 government specification  Shelf Life:  N/a	Terminal type per body style
Reliability Failure Rate Level In Percent:  0.010  Body Length:  0.050 inches  Body Width:  0.150 inches  Body Height:  Between 0.010 inches and 0.040 inches  Power Dissipation Rating In Watts:  0.100 free air  Unpackaged Unit Weight:  0.0001 grams  Style Designator:  Termination pad each end  Test Data Document:  81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81349-mil-r-55342/4 government specification  Shelf Life:  N/a	Reliability Indicator:
Body Length:  0.050 inches  Body Width:  0.150 inches  Body Height:  Between 0.010 inches and 0.040 inches  Power Dissipation Rating In Watts:  0.100 free air  Unpackaged Unit Weight:  0.0001 grams  Style Designator:  Termination pad each end  Test Data Document:  81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81349-mil-r-55342/4 government specification  Shelf Life:  N/a	Established
Body Length:  0.050 inches  Body Width:  0.150 inches  Body Height:  Between 0.010 inches and 0.040 inches  Power Dissipation Rating In Watts:  0.100 free air  Unpackaged Unit Weight:  0.0001 grams  Style Designator:  Termination pad each end  Test Data Document:  81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81349-mil-r-55342/4 government specification  Shelf Life:	Reliability Failure Rate Level In Percent:
0.050 inches  Body Width: 0.150 inches  Body Height:  Between 0.010 inches and 0.040 inches  Power Dissipation Rating In Watts: 0.100 free air  Unpackaged Unit Weight: 0.0001 grams  Style Designator:  Termination pad each end  Test Data Document: 81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data: 81349-mil-r-55342/4 government specification  Shelf Life: N/a	0.010
Body Width:  0.150 inches  Body Height:  Between 0.010 inches and 0.040 inches  Power Dissipation Rating In Watts:  0.100 free air  Unpackaged Unit Weight:  0.0001 grams  Style Designator:  Termination pad each end  Test Data Document:  81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81349-mil-r-55342/4 government specification  Shelf Life:  N/a	Body Length:
0.150 inches  Body Height: Between 0.010 inches and 0.040 inches  Power Dissipation Rating In Watts: 0.100 free air  Unpackaged Unit Weight: 0.0001 grams  Style Designator:  Termination pad each end  Test Data Document: 81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data: 81349-mil-r-55342/4 government specification  Shelf Life: N/a	0.050 inches
Between 0.010 inches and 0.040 inches  Power Dissipation Rating In Watts: 0.100 free air  Unpackaged Unit Weight: 0.0001 grams  Style Designator:  Termination pad each end  Test Data Document: 81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data: 81349-mil-r-55342/4 government specification  Shelf Life: N/a	Body Width:
Between 0.010 inches and 0.040 inches  Power Dissipation Rating In Watts: 0.100 free air  Unpackaged Unit Weight: 0.0001 grams  Style Designator:  Termination pad each end  Test Data Document: 81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data: 81349-mil-r-55342/4 government specification  Shelf Life: N/a	0.150 inches
Power Dissipation Rating In Watts:  0.100 free air  Unpackaged Unit Weight:  0.0001 grams  Style Designator:  Termination pad each end  Test Data Document:  81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81349-mil-r-55342/4 government specification  Shelf Life:  N/a	Body Height:
O.100 free air  Unpackaged Unit Weight:  0.0001 grams  Style Designator:  Termination pad each end  Test Data Document:  81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81349-mil-r-55342/4 government specification  Shelf Life:  N/a	Between 0.010 inches and 0.040 inches
Unpackaged Unit Weight:  0.0001 grams  Style Designator:  Termination pad each end  Test Data Document:  81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81349-mil-r-55342/4 government specification  Shelf Life:  N/a	Power Dissipation Rating In Watts:
O.0001 grams  Style Designator:  Termination pad each end  Test Data Document:  81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81349-mil-r-55342/4 government specification  Shelf Life:  N/a	0.100 free air
Style Designator:  Termination pad each end  Test Data Document:  81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81349-mil-r-55342/4 government specification  Shelf Life:  N/a	Unpackaged Unit Weight:
Termination pad each end  Test Data Document:  81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81349-mil-r-55342/4 government specification  Shelf Life:  N/a	0.0001 grams
Test Data Document:  81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81349-mil-r-55342/4 government specification  Shelf Life:  N/a	Style Designator:
81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81349-mil-r-55342/4 government specification  Shelf Life:  N/a	Termination pad each end
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81349-mil-r-55342/4 government specification  Shelf Life:  N/a	Test Data Document:
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data: 81349-mil-r-55342/4 government specification  Shelf Life: N/a	81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data: 81349-mil-r-55342/4 government specification  Shelf Life: N/a	format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
Specification Data: 81349-mil-r-55342/4 government specification Shelf Life: N/a	
81349-mil-r-55342/4 government specification  Shelf Life: N/a	
Shelf Life: N/a	
N/a	
<del></del>	<del></del>

No

Demilitarization:

## NSN 5905-01-266-7717

Film Fixed Resistor - Page 2 of 2



Fiig:

A001a0