## NSN 5905-01-267-1301

N/a

Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-267-1301

| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:   |
|---|
| -150.0/+150.0   |
| Electrical Resistance:  |
| 3.400 kilohms   |
| Resistance Tolerance In Percent:  |
| -5.000/+1.000   |
| Ambient Tempurature In Deg Celsius At Full Rated Power:   |
| 70.0  |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:   |
| 125.0   |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius:  |
| -55.0/+125.0  |
| Inclosure Method:   |
| Encapsulated  |
| Terminal Quantity:  |
| 16  |
| Terminal Type:  |
| Tab, solder lug   |
| Reliability Indicator:  |
| Not established   |
| Terminal Length:  |
| Between 0.125 inches and 0.150 inches   |
| Body Length:  |
| Between 0.784 inches and 0.876 inches   |
| Body Width:   |
| Between 0.220 inches and 0.310 inches   |
| Body Height:  |
| 0.200 inches  |
| Schematic Diagram Designator:   |
| Isolated array  |
| Power Dissipation Rating In Watts:  |
| 1.500 total network   |
| Terminal Width:   |
| Between 0.014 inches and 0.200 inches   |
| End Application:  |
| 5805-01-216-0887 telephone equipment  |
| Identical Value Resistor Quantity:  |
| 1 lowest resistance value1 highest resistance value1 1st intermediate resistance value1 2nd intermediate resistance value3 3rd intermediate |
| resistance value1 4th intermediate resistance value1 5th intermediate resistance value1 6th intermediate resistance value1 7th intermediate |
| resistance value  |
| Style Designator:   |
| Dual inline   |
| Shelf Life:   |

## NSN 5905-01-267-1301

Film Fixed Resistor Network - Page 2 of 2



|   |    | • • |             |          |  |
|---|----|-----|-------------|----------|--|
| ш | ın | 10  | <i>(</i> )+ | Measure: |  |
|   |    |     |             |          |  |

--

Demilitarization:

No

Fiig:

A001a0