

View Online at <https://aerobasegroup.com/nsn/5905-01-267-2243>

**Section Quantity:**

1

**Body Style:**

Cylindrical servo mounted

**Reliability Indicator:**

Not established

**Pilot Diameter:**

0.7500 inches

**Pilot Length:**

0.0620 inches

**Undercut Diameter:**

0.781 inches

**Undercut Width:**

0.0570 inches

**Body Diameter:**

1.062 inches

**Shaft Diameter:**

0.125 inches

**Shaft Length:**

0.750 inches

**Body Length:**

0.810 inches

**Mounting Lip Diameter:**

0.8750 inches

**Mounting Lip Depth:**

0.0620 inches

**Shaft Style:**

Round

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

320.0

**Maximum Starting Torque:**

5.00 inch-ounces

**Maximum Running Torque:**

4.00 inch-ounces

**Shaft End Play:**

0.005 inches

**Shaft Runout:**

0.002 inches

**Lateral Runout:**

0.002 inches

**Pilot Diameter Runout:**

0.001 inches

**Shaft Radial Play:**

0.002 inches

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Clamp ring

**Electrical Resistance Per Section:**

10.0 kilohms single section

**Rotary Actuator Travel In Angular Deg:**

360.0

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

125.0 single section

**Power Dissipation Rating Per Section In Watts:**

1.0 free air single section

**Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 single section

**Actuator Travel Control Feature:**

Continuous motion

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

70.0 single section

**Standard Taper Curve Per Section:**

A single section

**Test Data Document:**

81349-mil-r-39023 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

3 tab, solder lug

**Specification Data:**

81349-mil-r-39023/1 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A002a0