NSN 5905-01-267-3884

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-01-267-3884 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 1.750 inches First Flat Length: 0.312 inches Flat Height: 0.094 inches **Body Diameter:** 0.906 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.750 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 0.433 inches **Overall Diameter:** 1.266 inches **Shaft Style:** Round, flatted **Shaft Bearing Type:** Sleeve Switch Type: Rotary **Switch Voltage Rating In Volts:** 117.0 **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 338.0 **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:**

0.438 inchesSwitch Operating Position:Start of rotation

NSN 5905-01-267-3884

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 3



Switch Contact Arrangement:
Single pole, single throw, normally closed
Fragility Factor:
Moderately rugged
Screw Thread Diameter:
0.250 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Rear-bottom
Mounting Method:
Standard bushing
Features Provided:
Humidity proof and switch
Cubic Measure:
3.310 cubic inches
Electrical Resistance Per Section:
500.0 ohms single section
Rotary Actuator Travel In Angular Deg:
338.0
Resistance Tempurature Characteristic Range Per Section In Percent:
$-3.0/+0.0 -55 \ degrees \ celsius \ single \ section \ and \ -5.0/+10.0 -25 \ degrees \ celsius \ single \ section \ and \ -5.0/+10.0 \ 25 \ degrees \ section \ and \ -5.0/+10.0 \ 25 \ degrees \ and \ section \ and \ -5.0/+10.0 \ and \ and \ -5.0/+10.0 \ a$
section and +0.0/+3.0 120 degrees celsius single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
120.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Switch Current Type And Rating In Amps:
3.000 ac/dc
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
5 tab, solder lug
Shelf Life:

-

N/a

Unit Of Measure:

NSN 5905-01-267-3884

Nonprecision Nonwire Wound Variable Resistor - Page 3 of 3



Der	nilit	ariz	atio	n:

No

Fiig:

A002a0