NSN 5905-01-267-3930

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-267-3930 **Section Quantity:** 1 **Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Established **Reliability Failure Rate Level In Percent:** 0.100 **Mounting Hole Diameter:** 0.093 inches **Shaft Diameter:** 0.115 inches **Shaft Length:** 0.058 inches **Body Length:** 1.250 inches **Body Width:** 0.190 inches **Body Height:** 0.315 inches **Shaft Style:** Round, slotted **Shaft Bearing Type:** Sleeve **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** Between 6120.0 and 9720.0 **Maximum Starting Torque:** 8.00 inch-ounces **Maximum Running Torque:** 8.00 inch-ounces **Lateral Distance Between Mounting Hole Centers:**

1.000 inches **Mounting Facility Quantity: Terminal Location:** Lower adjacent side two rows **Mounting Method:** Unthreaded hole **Cubic Measure:** 0.075 cubic inches

NSN 5905-01-267-3930

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Flectrical	Resistance	Per	Section:
Licuitai	Nesisiance	1 61	occion.

2.0 percent, rated amperes c and better flooring

Rotary Actuator Travel In Angular Deg:

Between 6120.0 and 9720.0

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0/+100.0 single section

Power Dissipation Rating Per Section In Watts:

0.75 7th secondary quality

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Actuator Travel Control Feature:

Clutch

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

Standard Taper Curve Per Section:

A single section

Test Data Document:

81349-mil-r-39035 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

3 wire lead

Specification Data:

81349-mil-r-39035/1 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No Fiig:

A002a0