## NSN 5905-01-267-3931

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-267-3931 **Section Quantity:** 1 **Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Established **Reliability Failure Rate Level In Percent:** 0.100 **Mounting Hole Diameter:** 0.093 inches **Shaft Diameter:** 0.115 inches **Shaft Length:** 0.058 inches **Body Length:** 1.250 inches **Body Width:** 0.190 inches **Body Height:** 0.315 inches **Shaft Style:** Round, slotted **Shaft Bearing Type:** Sleeve **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** Between 6120.0 and 9720.0 **Maximum Starting Torque:** 8.00 inch-ounces **Maximum Running Torque:** 8.00 inch-ounces **Lateral Distance Between Mounting Hole Centers:** 1.000 inches **Mounting Facility Quantity:** 

**Terminal Location:** Lower adjacent side two rows **Mounting Method:** Unthreaded hole **Cubic Measure:** 0.075 cubic inches

## NSN 5905-01-267-3931

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



<b>Flectrical</b>	Resistance	Per Section:

20.0 percent, rated amperes c and better flooring

**Rotary Actuator Travel In Angular Deg:** 

Between 6120.0 and 9720.0

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0/+100.0 single section

**Power Dissipation Rating Per Section In Watts:** 

0.75 7th secondary quality

**Resistance Tolerance Per Section In Percent:** 

-10.0/+10.0 single section

**Actuator Travel Control Feature:** 

Clutch

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

**Standard Taper Curve Per Section:** 

A single section

**Test Data Document:** 

81349-mil-r-39035 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:** 

3 wire lead

**Specification Data:** 

81349-mil-r-39035/1 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

\_

**Demilitarization:** 

No Fiig:

A002a0