Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-267-7112

Section Quantity:
1
Body Style:
Rectangular
Reliability Indicator:
Established
Reliability Failure Rate Level In Percent:
0.010
Terminal Length:
0.300 inches
Shaft Diameter:
0.075 inches
Shaft Length:
0.080 inches
Body Length:
0.420 inches
Body Width:
0.170 inches
Body Height:
0.375 inches
Shaft Style:
Round, slotted
Shaft Bearing Type:
Sleeve
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
Between 5400.0 and 10800.0
Maximum Starting Torque:
5.00 inch-ounces
Maximum Running Torque:
5.00 inch-ounces
Center To Center Distance Between Terminals:
0.200 inches
Terminal Location:
Left adjacent side two rows
Mounting Method:
Terminal
Center To Center Distance Between Terminal Rows:
0.100 inches
Cubic Measure:
0.024 cubic inches

NSN 5905-01-267-7112

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section: 500.0 percent, rated amperes c and better flooring **Rotary Actuator Travel In Angular Deg:** Between 5400.0 and 10800.0 Center To Center Distance Between Center Terminal And Outside Terminal: 0.100 inches Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 150.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -250.0/+250.0 single section **Power Dissipation Rating Per Section In Watts:** 0.5 7th secondary quality **Resistance Tolerance Per Section In Percent:** -10.0/+10.0 single section **Actuator Travel Control Feature:** Clutch Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 85.0 single section Standard Taper Curve Per Section: A single section **Test Data Document:** 81349-mil-r-39035 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 3 pin **Specification Data:** 81349-mil-r-39035/2 government specification Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A002a0