NSN 5905-01-267-9276

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-267-9276

Seedien Overstitus
Section Quantity:
Body Style:
Cylindrical servo mounted
Reliability Indicator:
Not established
Undercut Diameter:
0.875 inches
Undercut Width:
0.0620 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.312 inches
Body Length:
1.828 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Maximum Running Torque:
2.00 inch-ounces
Shaft End Play:
0.015 inches
Shaft Radial Play:
0.005 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Longitudinally positioned on the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
100.0 kilohms single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
85.0 single section
Power Dissipation Rating Per Section In Watts:

2.0 free air single section

NSN 5905-01-267-9276

Precision Wire Wound Variable Resistor - Page 2 of 2



Resis	stance	Tolerance	Per	Section	In l	Percent:

-5.0/+5.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

25.0 single section

Terminal Type And Quantity:

3 turret

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0