NSN 5905-01-268-2661

Precision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-268-2661

Section Quantity:
1
Body Style:
Rectangular bushing mounted
Reliability Indicator:
Not established
First Flat Length:
0.625 inches
Flat Height:
0.216 inches
Shaft Diameter:
0.250 inches
Shaft Length:
2.000 inches
Mounting Bushing Length:
0.375 inches
Body Length:
0.594 inches
Body Width:
0.625 inches
Body Height:
0.625 inches
Shaft Style:
Round, flat, undercut
Actuator Type:
Single shaft
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Lower adjacent side two rows
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
500.0 ohms single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
120.0 single section
Power Dissipation Rating Per Section In Watts:

1.0 free air single section

NSN 5905-01-268-2661

Precision Nonwire Wound Variable Resistor - Page 2 of 2



-20.0/+20.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

Unit Of Measure:

N/a

Demilitarization:

No

Fiig:

A002a0