NSN 5905-01-268-3877

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-268-3877

Seedien Overstitus
Section Quantity:
Body Style:
Rectangular bushing mounted
Reliability Indicator:
Not established
Terminal Length:
0.203 inches
Shaft Diameter:
0.125 inches
Shaft Length:
0.750 inches
Mounting Bushing Length:
0.500 inches
Body Length:
0.531 inches
Body Width:
0.625 inches
Body Height:
0.625 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Screw Thread Diameter:
0.250 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Right-left adjacent sides
Mounting Method:
Locking bushing
Electrical Resistance Per Section:
10.000 kilohms single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
120.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Function Conformity Per Section:

Single section independent linearity

NSN 5905-01-268-3877

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



-20.0/+20.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

4 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0