NSN 5905-01-268-7158

Precision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-268-7158 **Section Quantity: Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** Between 0.9683 inches and 0.9688 inches Pilot Length: Between 0.0570 inches and 0.0670 inches **Undercut Diameter:** 0.975 inches **Undercut Width:** 0.0570 inches **Body Diameter:** 1.090 inches **Shaft Diameter:** Between 0.1244 inches and 0.1247 inches **Shaft Length:** Between 0.968 inches and 1.000 inches **Body Length:** 0.620 inches **Mounting Lip Diameter:** Between 1.0570 inches and 1.0670 inches **Mounting Lip Depth:** Between 0.0570 inches and 0.0670 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Clamp ring **Fixed Tap Quantity Per Section:** 1 single section **Terminal Type And Quantity:** 4 turret Shelf Life: N/a

Unit Of Measure:

NSN 5905-01-268-7158

Precision Nonwire Wound Variable Resistor - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A002a0