Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-268-7517

## Section Quantity:

1

Body Style:

Rectangular w/pointer adjustment

### **Reliability Indicator:**

Not established

### **Terminal Length:**

0.157 inches

**Body Length:** 

0.236 inches

**Body Width:** 

0.591 inches

Body Height:

#### 0.673 inches

Actuator Type:

#### Recessed drive with slot

### Effective Electrical Rotation In Deg Angular Rotation:

250.0

### Center To Center Distance Between Terminals:

0.346 inches

#### **Terminal Location:**

Lower adjacent side two rows

#### Mounting Method:

Terminal

### Center To Center Distance Between Terminal Rows:

0.157 inches

#### **Electrical Resistance Per Section:**

1.0 megohms single section

#### **Rotary Actuator Travel In Angular Deg:**

265.0

## Center To Center Distance Between Center Terminal And Outside Terminal:

0.173 inches

## Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

70.0 single section

# Power Dissipation Rating Per Section In Watts:

0.250 free air single section

## **Resistance Tolerance Per Section In Percent:**

-25.0/+70.0 all sections

## Actuator Travel Control Feature:

Stops

## Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Standard Taper Curve Per Section:

A single section

#### **Special Features:**

W/spindle

Test Data Document:

57705-02-2207 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

3 pin, preformed

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0