Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-269-1085

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

First Flat Length:

0.250 inches

Flat Height:

0.094 inches

Body Diameter:

0.500 inches

Shaft Diameter:

Between 0.124 inches and 0.125 inches

Shaft Length:

0.625 inches

Mounting Bushing Length:

0.250 inches

Body Length:

0.469 inches

Shaft Style:

Round, flatted

Actuator Type:

Single shaft

End Application:

Bqr-23 (v)

Screw Thread Diameter:

0.250 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Rear end

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

5.0 kilohms single section

Power Dissipation Rating Per Section In Watts:

0.5 free air single section

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section



Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0