Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-269-4183

## Section Quantity:

1

Body Style:

Rectangular

## **Reliability Indicator:**

Not established

#### **Terminal Length:**

2.000 inches

**Body Length:** 

0.190 inches

**Body Width:** 

#### 0.375 inches

Body Height:

#### 0.375 inches

Actuator Type:

#### Flush drive with slot-hole

#### Effective Electrical Rotation In Deg Angular Rotation:

280.0

#### Maximum Starting Torque:

5.00 inch-ounces

## Maximum Running Torque:

5.00 inch-ounces

## Center To Center Distance Between Terminals:

2.000 inches

#### **Terminal Location:**

Upper adjacent side single row

#### Mounting Method:

Terminal

#### **Electrical Resistance Per Section:**

10.0 kilohms single section

#### **Rotary Actuator Travel In Angular Deg:**

310.0

## Center To Center Distance Between Center Terminal And Outside Terminal:

1.000 inches

## Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

# Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0/+100.0 single section

# Power Dissipation Rating Per Section In Watts:

0.5 free air single section

# **Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 single section

# NSN 5905-01-269-4183

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Actuator Travel Control Feature:

Stops

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 pin

**Purchase Description Identification:** 

57705-02-2236

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0