## NSN 5905-01-269-5880

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-269-5880 **Section Quantity: Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 0.875 inches **Shaft Diameter:** Between 0.1245 inches and 0.1248 inches **Shaft Length:** 0.500 inches **Mounting Bushing Length:** Between 0.344 inches and 0.406 inches **Body Length:** Between 0.428 inches and 0.458 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Shaft Runout:** 0.001 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 1000.0 ohms single section **Power Dissipation Rating Per Section In Watts:** 1.0 free air single section **Resistance Tolerance Per Section In Percent:** -10.0/+10.0 single section **Terminal Type And Quantity:** 2 turret Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5905-01-269-5880

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



_		••	• •					
וו	em	ш	112	r17	2+	$\sim$	n	
$\boldsymbol{-}$	CIII	••	ıιa	114	.aı	ı		

No

Fiig:

A002a0