## NSN 5905-01-269-5963

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-269-5963

•
Section Quantity:
2
Body Style:
Rectangular bushing mounted
Reliability Indicator:
Not established
Overall Length:
1.761 inches
Terminal Length:
0.100 inches
First Flat Length:
Between 0.255 inches and 0.275 inches
Flat Height:
Between 0.129 inches and 0.135 inches
Shaft Diameter:
Between 0.169 inches and 0.175 inches
Shaft Length:
Between 0.760 inches and 0.800 inches
Mounting Bushing Length:
Between 0.360 inches and 0.390 inches
Body Length:
Between 0.870 inches and 0.930 inches
Body Width:
Between 0.610 inches and 0.640 inches
Body Height:
Between 0.610 inches and 0.640 inches
Shaft Style:
Round, flatted
Shaft Bearing Type:
Sleeve
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
360.0
Maximum Starting Torque:
4.50 inch-ounces
Maximum Running Torque:
1.50 inch-ounces
Nonturn Device Location:
At 9 oclock

**Nonturn Device Radius:** 

Between 0.305 inches and 0.320 inches

## NSN 5905-01-269-5963

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Center To Center Distance Between Terminals:
Between 0.180 inches and 0.220 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Rear end
Mounting Method:
Standard bushing
Features Provided:
Nonmetallic shaft
Cubic Measure:
0.381 cubic inches
Electrical Resistance Per Section:
5.0 percent, rated amperes c and better
Rotary Actuator Travel In Angular Deg:
360.0
Center To Center Distance Between Center Terminal And Outside Terminal:
0.090 mils and 0.110 centimeters
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 all sections
Power Dissipation Rating Per Section In Watts:
0.25 7th secondary at 10'30 oclock
Resistance Tolerance Per Section In Percent:
-30.0/+30.0 all sections
Actuator Travel Control Feature:
Continuous motion
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 all sections
Standard Taper Curve Per Section:
A all sections
Terminal Type And Quantity:
6 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0