Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-269-5964

Section Quantity:

1

Body Style:

Cylindrical

Reliability Indicator:

Not established

Terminal Length:

0.300 inches

Body Diameter:

0.287 inches

Body Length:

0.244 inches

Actuator Type:

Flush drive with slot-hole

Maximum Starting Torque:

5.00 inch-ounces

Maximum Running Torque:

5.00 inch-ounces

Center To Center Distance Between Terminals:

Between 0.180 inches and 0.220 inches

Terminal Location:

Rear end

Mounting Method:

Terminal

Cubic Measure:

0.016 cubic inches

Electrical Resistance Per Section:

100.0 kilohms single section

Center To Center Distance Between Center Terminal And Outside Terminal:

Between 0.090 inches and 0.110 inches

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

Power Dissipation Rating Per Section In Watts:

0.5 free air single section

Resistance Tolerance Per Section In Percent:

-20.0/+20.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 pin

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0