

View Online at <https://aerobasegroup.com/nsn/5905-01-269-9912>

Electrical Resistance:

1000.0 ohms and 750.0 ohms and 120.0 ohms and 2.43 kilohms and 3.92 kilohms and 2.4 kilohms and 6.8 kilohms and 330.0 ohms and 5.1 kilohms and 62.0 kilohms and 5.1 kilohms

Resistance Tolerance In Percent:

-2.0/+2.0 and -2.0/+2.0 and -2.0/+2.0 and -1.0/+1.0 and -1.0/+1.0 and -0.50/+0.50 and -2.0/+2.0 and -2.0/+2.0 and -2.0/+2.0 and -2.0/+2.0 and -2.0/+2.0

Terminal Quantity:

4 and 2 and 4 and 4 and 2 and 6 and 16 and 16 and 12 and 6 and 4

Terminal Type:

Wire lead and wire lead and wire lead and wire lead and wire lead and wire lead and wire lead and wire lead and wire lead and wire lead and wire lead

Resistor Power Dissipation Rating In Watts:

2.0 and 2.0 and 2.0 and 3.0 and 7.0 and 7.0 and 1.0 and 1.0 and 0.25 and 0.125 and 0.5

Mounting Method:

Solder

Component Quantity:

2 and 1 and 2 and 2 and 1 and 3 and 8 and 8 and 6 and 3 and 2

Component Controlling Agency:

Hercules

Component Name:

Fixed film resistors; fixed wire wound resistors

Component Identifying Number:

-22684/8/1097 part no. And -22684/8/1091 part no. And -22684/8/1053 part no. And rwr89s2430fm part no. And rwr84s3920fr part no. And rwr84s2400dr part no. And rlr32c6800gm part no. And rlr32c331gm part no. And rlr07c5101gr part no. And rlr05c6202gr part no. And rlr20c5101gr part no.

Assembly Construction Method:

Mounted on printed circuit board

Component Relationship:

Not matched

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T172-f