NSN 5905-01-270-1695

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-270-1695 **Section Quantity: Body Style:** Rectangular **Reliability Indicator:** Not established **Terminal Length:** Between 0.025 inches and 0.055 inches **Shaft Diameter:** Between 0.055 inches and 0.085 inches **Shaft Length:** 0.040 inches **Body Length:** Between 0.230 inches and 0.270 inches **Body Width:** Between 0.235 inches and 0.265 inches **Body Height:** Between 0.155 inches and 0.185 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 4320.0 **Maximum Starting Torque:** 3.00 inch-ounces **Maximum Running Torque:** 3.00 inch-ounces **Center To Center Distance Between Terminals:** Between 0.180 inches and 0.220 inches **Terminal Location:** Front-rear **Mounting Method: Terminal Cubic Measure:** 0.013 cubic inches **Electrical Resistance Per Section:** 20.0 kilohms single section **Rotary Actuator Travel In Angular Deg:**

5760.0

Center To Center Distance Between Center Terminal And Outside Terminal:

Between 0.090 inches and 0.110 inches

NSN 5905-01-270-1695

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Ambient	Tempurature	In Deg	Celsius	Per Section	At Zero	Percent	Rated Power:
---------	--------------------	--------	---------	-------------	---------	---------	--------------

150.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0/+100.0 single section

Power Dissipation Rating Per Section In Watts:

0.25 free air single section

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Actuator Travel Control Feature:

Clutch

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

Standard Taper Curve Per Section:

A single section

Test Data Document:

04939-+39035-006 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

_

Demilitarization:

No

Fiig:

A002a0