NSN 5905-01-270-9983

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-270-9983

| Section Quantity: |
|--|
| 1 |
| Body Style: |
| Rectangular bushing mounted |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| 0.500 inches |
| Shaft Diameter: |
| 0.125 inches |
| Shaft Length: |
| 0.875 inches |
| Mounting Bushing Length: |
| 0.375 inches |
| Body Length: |
| 0.625 inches |
| Body Width: |
| 0.625 inches |
| Body Height: |
| 0.625 inches |
| Shaft Style: |
| Round, slotted |
| Actuator Type: |
| Single shaft |
| Effective Electrical Rotation In Deg Angular Rotation: |
| 240.0 |
| Center To Center Distance Between Terminals: |
| 0.200 inches |
| Screw Thread Diameter: |
| 0.375 inches |
| Screw Thread Series Designator: |
| Unef |
| Screw Thready Qty Per Inch (tpi): |
| 32.0 |
| Terminal Location: |
| Lower adjacent side two rows |
| Mounting Method: |
| Standard bushing |
| Center To Center Distance Between Terminal Rows: |
| 0.200 inches |
| Flactrical Resistance Per Section: |

50.0 kilohms single section

NSN 5905-01-270-9983

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



| Rotary Actuator Travel In Angular Deg: |
|---|
| 300.0 |
| Center To Center Distance Between Center Terminal And Outside Terminal: |
| 0.200 inches |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: |
| 120.0 single section |
| Power Dissipation Rating Per Section In Watts: |
| 2.0 free air single section |
| Resistance Tolerance Per Section In Percent: |
| -10.0/+10.0 single section |
| Actuator Travel Control Feature: |
| Stops |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: |
| 70.0 single section |
| Standard Taper Curve Per Section: |
| A single section |
| Terminal Type And Quantity: |
| 3 pin |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A002a0 |