

View Online at <https://aerobasegroup.com/nsn/5905-01-271-5357>

Section Quantity:

2

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Body Diameter:

0.940 inches

Shaft Diameter:

0.250 inches

Shaft Length:

1.300 inches

Mounting Bushing Length:

0.375 inches

Body Length:

0.880 inches

Undercut Diameter:

0.125 inches

Shaft Style:

Round, stepped

Shaft Bearing Type:

Sleeve

Actuator Type:

Dual concentric

Effective Electrical Rotation In Deg Angular Rotation:

300.0

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

0.440 inches

Fragility Factor:

Moderately rugged

Undercut Length:

0.425 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Features Provided:

Humidity proof

Electrical Resistance Per Section:

50.0 percent, rated amperes c and better industrial clears

Rotary Actuator Travel In Angular Deg:

300.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

85.0 all sections

Power Dissipation Rating Per Section In Watts:

0.5 7th secondary finish

Resistance Tolerance Per Section In Percent:

-30.0/+30.0 all sections

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

55.0 all sections

Standard Taper Curve Per Section:

A all sections

Test Data Document:

13499-376-0276 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0