## NSN 5905-01-272-0040

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-272-0040 **Section Quantity: Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 1.000 inches **Shaft Length:** 18.0 millimeters **Mounting Bushing Length:** 10.0 millimeters **Shaft Style:** Round **Actuator Type:** Single shaft **End Application:** Whidbey island class lsd, spruance class d (963), kidd class ddg, oliver perry class ffg, los angeles class ssn(688), ticonderoga class cg(47), forrestal class cv, avenger class mcm, nimitz class cvn **Terminal Location:** Radially positioned over less than half the circumference **Electrical Resistance Per Section:** 10.0 kilohms single section **Function Conformity Tolerance Per Section:** -0.25/+0.25 single section **Function Conformity Per Section:** Single section independent linearity **Resistance Tolerance Per Section In Percent:** -5.0/+5.0 single section **Criticality Code Justification:** Feat **Function Characteristic Per Section:** Single section linear **Special Features:** Weapons system essential **Terminal Type And Quantity:** 3 tab, solder lug

Demilitarization:

**Unit Of Measure:** 

Shelf Life:

No

N/a

## NSN 5905-01-272-0040

Precision Wire Wound Variable Resistor - Page 2 of 2



Fiig:

A002a0