

View Online at <https://aerobasegroup.com/nsn/5905-01-272-4323>

**Section Quantity:**

1

**Body Style:**

Rectangular bushing mounted

**Reliability Indicator:**

Not established

**Terminal Length:**

0.602 inches

**First Flat Length:**

0.313 inches

**Flat Height:**

0.216 inches

**Shaft Diameter:**

0.250 inches

**Shaft Length:**

0.875 inches

**Mounting Bushing Length:**

0.375 inches

**Body Length:**

0.500 inches

**Body Width:**

0.625 inches

**Body Height:**

0.625 inches

**Shaft Style:**

Round, flatted

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

240.0

**Maximum Starting Torque:**

0.50 inch-ounces

**Maximum Running Torque:**

1.50 inch-ounces

**Maximum Stop Torque:**

64.00 inch-ounces

**Center To Center Distance Between Terminals:**

0.200 inches

**Fragility Factor:**

Moderately rugged

**Screw Thread Diameter:**

0.375 inches

**Screw Thread Series Designator:**

Unef

**Screw Thread Qty Per Inch (tpi):**

32.0

**Terminal Location:**

Lower adjacent side single row

**Mounting Method:**

Standard bushing

**Features Provided:**

Nonmetallic shaft and humidity proof

**Cubic Measure:**

0.1953125 cubic inches

**Electrical Resistance Per Section:**

1.0 ohms and better flooring

**Rotary Actuator Travel In Angular Deg:**

300.0

**Center To Center Distance Between Center Terminal And Outside Terminal:**

0.100 inches

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

125.0 single section

**Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:**

-150.0/+150.0 single section

**Power Dissipation Rating Per Section In Watts:**

2.0 7th secondary quality

**Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 single section

**Actuator Travel Control Feature:**

Stops

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

70.0 single section

**Standard Taper Curve Per Section:**

A single section

**Terminal Type And Quantity:**

3 pin

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0