Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-272-7194

# Section Quantity:

1

Body Style:

Cylindrical bushing mounted

# **Reliability Indicator:**

Not established

### **Body Diameter:**

1.220 inches

#### Shaft Diameter:

0.250 inches

#### Shaft Length:

1.250 inches

### Mounting Bushing Length:

0.500 inches

### Body Length:

0.620 inches

# Shaft Style:

Round, slotted

# Actuator Type:

Single shaft

### Effective Electrical Rotation In Deg Angular Rotation:

Between 220.0 and 285.0

# Maximum Starting Torque:

6.00 inch-ounces

### Maximum Running Torque:

6.00 inch-ounces

### Maximum Stop Torque:

128.00 inch-ounces

### Nonturn Device Location:

At 9 oclock

### Nonturn Device Radius:

0.531 inches

### Fragility Factor:

Moderately rugged

### Screw Thread Diameter:

0.375 inches

### Screw Thread Series Designator:

Unef

### Screw Thready Qty Per Inch (tpi):

32.0

### **Terminal Location:**

Radially positioned over less than half the circumference



**Mounting Method:** Standard bushing **Features Provided:** Humidity proof and panel seal **Electrical Resistance Per Section:** 3.5 kilohms single section **Rotary Actuator Travel In Angular Deg:** Between 290.0 and 305.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 105.0 single section **Power Dissipation Rating Per Section In Watts:** 2.0 free air single section **Resistance Tolerance Per Section In Percent:** -10.0/+10.0 single section **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section **Standard Taper Curve Per Section:** A single section **Test Data Document:** 81349-mil-r-19 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 3 tab, solder lug **Specification Data:** 81349-mil-r-19/2 government specification Shelf Life: N/a Unit Of Measure: **Demilitarization:** Fiig: A002a0

---

No