NSN 5905-01-272-8179

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-272-8179 **Section Quantity: Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 1.590 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 1.250 inches **Mounting Bushing Length:** 0.500 inches **Body Length:** 0.620 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** Between 230.0 and 275.0 **Maximum Starting Torque:** 6.00 inch-ounces **Maximum Running Torque:** 6.00 inch-ounces **Maximum Stop Torque:** 128.00 inch-ounces **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:** 0.531 inches **Fragility Factor:** Moderately rugged **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0

Terminal Location:

Radially positioned over less than half the circumference

NSN 5905-01-272-8179

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Mounting Method:
Standard bushing
Features Provided:
Humidity proof
Electrical Resistance Per Section:
25.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
Between 280.0 and 305.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
105.0 single section
Power Dissipation Rating Per Section In Watts:
4.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Standard Taper Curve Per Section:
A single section
Test Data Document:
81349-mil-r-19 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formation
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
3 tab, solder lug
Specification Data:
81349-mil-r-19/3 government specification
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A002a0