NSN 5905-01-272-9575

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-01-272-9575

250.0/4350.0 Electrical Resistance: .0.020 ohms Resistance Tolerance in Percent: .3.000/43.000 Ambient Tempurature in Deg Celsius At Full Rated Power: .25.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: .275.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: .55.0/4275.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: .55.0/4275.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: .55.0/4275.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: .55.0/4275.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: .55.0/4275.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: .55.0/4275.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: .55.0/4275.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: .55.0/4275.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: .55.0/4275.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: .55.0/4275.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: .55.0/4275.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: .55.0/4275.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: .55.0/4275.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: .55.0/4275.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: .55.0/4275.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: .55.0/4275.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: .55.0/4275.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: .55.0/4275.0 Tempurature Range Of Tem	Fempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Resistance Tolerance In Percent: 3.000/43.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/4275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Vot established Terminal Length: 2.000 inches Body Diameter: 2.250 inches Body Length: 2.075 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Aktal terminal each end Test Data Document: 2005368-7908753 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 20ctcludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Vol	350.0/+350.0
Resistance Tolerance in Percent: 3,000/43,000 Ambient Tempurature in Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0/4275.0 Inclosure Method: Encapsulated Terminal Type: Wife lead Reliability Indicator: Not established Terminal Length: 2,000 inches Body Diameter: 0,250 inches Body Length: 0,675 inches Power Dissipation Rating in Watts: 2,000 free air Style Designator: Axial terminal each end Test Data Document: 0,00536-7908753 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheff Life: Wa	Electrical Resistance:
Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 275.0 Tempurature Range Off Tempurature Coefficient In Deg Celsius: 275.0 Tempurature Range Off Tempurature Coefficient In Deg Celsius: 275.0 Tempurature Range Off Tempurature Coefficient In Deg Celsius: 275.0 Tempurature Range Off Tempurature Rang	0.020 ohms
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: 2.250 inches Body Length: 2.675 inches Power Dissipation Rating In Watts: 2.000 ree air Style Designator: Avial terminal each end Test Data Document: 20536-7908753 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 2xcludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Wa	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.04-275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.04-275.0 Inclosure Method: Increminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: 0.250 inches Body Diameter: 0.250 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Avail terminal each end Test Data Document: 00536-7908753 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Wa	3.000/+3.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: 0.250 inches Body Length: 0.675 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Avial terminal each end Test Data Document: 0.0536-7908753 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Wie	Ambient Tempurature In Deg Celsius At Full Rated Power:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Boddy Diameter: 2.250 inches Boddy Diameter: 2.050 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 30536-7908753 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Wa	25.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: 0.250 inches Body Length: 0.675 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 90536-7908753 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Wa	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
nclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Ferminal Length: 2.000 inches Body Diameter: 0.250 inches Body Diameter: 0.250 inches Body Length: 0.675 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Fest Data Document: 90536-7908753 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Wa	275.0
Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Ferminal Length: 2.000 inches Body Diameter: 0.250 inches Body Length: 0.675 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Fest Data Document: 90536-7908753 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Wa	empurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Ferminal Length: 2,000 inches Body Diameter: 0,250 inches Body Length: 0,675 inches Power Dissipation Rating In Watts: 2,000 free air Style Designator: Axial terminal each end Fest Data Document: 20536-7908753 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Wa	55.0/+275.0
Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2,000 inches Body Diameter: 0,250 inches Body Length: 0,675 inches Power Dissipation Rating In Watts: 2,000 free air Style Designator: Axial terminal each end Test Data Document: 0,0536-7908753 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Wa	nclosure Method:
Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: 0.250 inches Body Length: 0.675 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 00536-7908753 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Wa	Encapsulated
Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: 0.250 inches Body Length: 0.675 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 00536-7908753 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Wa	Ferminal Type:
Note established Terminal Length: 2.000 inches Body Diameter: 0.250 inches Body Length: 0.675 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 90536-7908753 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: W/a	Vire lead
Terminal Length: 2.000 inches Body Diameter: 0.250 inches Body Length: 0.675 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 90536-7908753 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: W/a	Reliability Indicator:
2.000 inches Body Diameter: 0.250 inches Body Length: 0.675 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Fest Data Document: 90536-7908753 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Wa	Not established
Body Diameter: 0.250 inches Body Length: 0.675 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 90536-7908753 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: W/a	Ferminal Length:
20.250 inches Body Length: 20.675 inches Power Dissipation Rating In Watts: 20.000 free air Style Designator: Axial terminal each end Test Data Document: 200536-7908753 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: W/a	2.000 inches
Body Length: 0.675 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 90536-7908753 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	Body Diameter:
2.000 free air Style Designator: Axial terminal each end Test Data Document: 90536-7908753 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life:	0.250 inches
Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 90536-7908753 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	Body Length:
2.000 free air Style Designator: Axial terminal each end Test Data Document: 90536-7908753 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life:	0.675 inches
Axial terminal each end Test Data Document: 90536-7908753 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	Power Dissipation Rating In Watts:
Axial terminal each end Test Data Document: 90536-7908753 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	2.000 free air
Test Data Document: 90536-7908753 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	Style Designator:
90536-7908753 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	Axial terminal each end
excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	Fest Data Document:
Shelf Life: N/a	90536-7908753 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
N/a	excludes any specification, standard or other document that may be referenced in a basic governing drawing)
	Shelf Life:
Jnit Of Measure:	√a
-	Jnit Of Measure:
	-
Demilitarization:	Demilitarization:
No	40
Filg:	Filg:
A001a0	A001a0