## NSN 5905-01-273-4006

Wirewound Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-273-4006

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
-2000.0/+2000.0
Electrical Resistance:
3.000 kilohms24.000 kilohms
Resistance Tolerance In Percent:
-0.100/+0.100
Ambient Tempurature In Deg Celsius At Full Rated Power:
25.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
70.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
+0.0/+70.0
Inclosure Method:
Encapsulated
Terminal Quantity:
8
Terminal Type:
Pin
Reliability Indicator:
Established
Reliability Failure Rate Level In Percent:
0.010
Terminal Length:
Between 0.150 inches and 0.250 inches
Body Length:
0.900 inches
Body Width:
0.650 inches
Body Height:
0.400 inches
Power Dissipation Rating In Watts:
0.100 each resistor and 0.600 each resistor
Identical Value Resistor Quantity:
2 lowest resistance value2 highest resistance value
Special Features:
One of the 24, 000 ohms resistor has a power rating of 0.1 watt
Style Designator:
Dual inline
Test Data Document:
10001-3254811 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc

excludes any specification, standard or other document that may be referenced in a basic governing drawing)

N/a

Shelf Life:

## NSN 5905-01-273-4006

Wirewound Fixed Resistor Network - Page 2 of 2



		• •			
ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A001a0