NSN 5905-01-273-4040

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-01-273-4040

Electrical Resistance: 1.000 kilohms Resistance Tolerance in Percent: -1.000 to 1.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0 to 150.0 Inclosure Method: Uninclosure Method: Uninclosure Method: Voit established Body Length: 0.040 inches Body Height: 0.050 inches Body Wildth: 0.050 inches Power Dissipation Rating in Watts: 0.125 free air Style Designator: Termination pad each end Test Data Document: Sex Celson Shard Rawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: No	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
1.000 kilohms Resistance Tolerance In Percent: -1.001 of 1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 150.0 Inclosure Method: Uninclosed Terminal Type: Terminal Type: Terminal type per body style Reliability Indicator: Not established Body Length: 0.040 inches Body Height: 0.050 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Termination pad each end Test Data Document: Sary11-5617798 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: No	-200.0 to 200.0
Resistance Tolerance In Percent: -1.000 to 1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 150.0 Inclosure Method: Uninclosed Terminal Type: Terminal Type: Terminal type per body style Reliability Indicator: Not established Body Length: 0.040 inches Body Width: 0.050 inches Body Height: 0.030 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Termination pad each end Test Data Document: 55711-5611798 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: No	Electrical Resistance:
Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 150.0 Inclosure Method: Uninclosed Terminal Type: Terminal type per body style Reliability Indicator: Not established Body Length: 0.040 inches Body Width: 0.050 inches Body Width: 0.030 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Terminaltop aeach end Test Data Document: 53711-5617798 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	1.000 kilohms
Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 150.0 Inclosure Method: Uninclosed Terminal Type: Terminal type per body style Reliability Indicator: Not established Body Length: 0.040 inches Body Width: 0.050 inches Body Width: 0.030 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Termination pad each end Test Data Document: 53711-5617798 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 150.0 Inclosure Method: Uninclosed Terminal Type: Terminal Type per body style Reliability Indicator: Not established Body Length: 0.040 inches Body Width: 0.050 inches Body Height: 0.030 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Terminaltyon pad each end Test Data Document: 53711-5617798 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	-1.000 to 1.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 150.0 Inclosure Method: Uninclosed Terminal Type: Terminal type per body style Reliability Indicator: Not established Body Length: 0.040 inches Body Width: 0.050 inches Body Width: 0.050 inches Body Height: 0.030 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Termination pad each end Test Data Document: 53711-5617798 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	Ambient Tempurature In Deg Celsius At Full Rated Power:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 150.0 Inclosure Method: Uninclosed Terminal Type: Terminal type per body style Reliability Indicator: Not established Body Length: 0.040 inches Body Width: 0.050 inches Body Height: 0.050 inches Body Height: 0.125 free air Style Designator: Terminaltyne per body style Reliability Indicator: Style Designator: Terminaltyne per body style Reliability Indicator: Style Designator: Terminaltyne per body style Reliability Indicator: Style Designation Rating In Watts: 0.175 free air Style Designator: Termination pad each end Test Data Document: 53711-5617798 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	70.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 150.0 Inclosure Method: Uninclosed Terminal Type: Terminal type per body style Reliability Indicator: Not established Body Length: 0.040 inches Body Width: 0.050 inches Body Height: 0.030 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Termination pad each end Test Data Document: 53711-5617798 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
Inclosure Method: Uninclosed Terminal Type: Terminal type per body style Reliability Indicator: Not established Body Length: 0.040 inches Body Width: 0.050 inches Body Height: 0.030 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Termination pad each end Test Data Document: 53711-5617798 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	150.0
Inclosure Method: Uninclosed Terminal Type: Terminal type per body style Reliability Indicator: Not established Body Length: 0.040 inches Body Width: 0.050 inches Body Height: 0.030 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Termination pad each end Test Data Document: 53711-5617798 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Uninclosed Terminal Type: Terminal type per body style Reliability Indicator: Not established Body Length: 0.040 inches Body Width: 0.050 inches Body Height: 0.030 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Termination pad each end Test Data Document: 53711-5617798 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	-55.0 to 150.0
Terminal Type: Terminal type per body style Reliability Indicator: Not established Body Length: 0.040 inches Body Width: 0.050 inches Body Height: 0.030 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Termination pad each end Test Data Document: 53711-5617798 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	Inclosure Method:
Terminal type per body style Reliability Indicator: Not established Body Length: 0.040 inches Body Width: 0.050 inches Body Height: 0.030 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Termination pad each end Test Data Document: 53711-5617798 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	Uninclosed
Reliability Indicator: Not established Body Length: 0.040 inches Body Width: 0.050 inches Body Height: 0.030 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Termination pad each end Test Data Document: 53711-5617798 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	Terminal Type:
Not established Body Length: 0.040 inches Body Width: 0.050 inches Body Height: 0.030 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Termination pad each end Test Data Document: 53711-5617798 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	Terminal type per body style
Body Length: 0.040 inches Body Width: 0.050 inches Body Height: 0.030 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Termination pad each end Test Data Document: 53711-5617798 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	Reliability Indicator:
Body Width: 0.050 inches Body Height: 0.030 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Termination pad each end Test Data Document: 53711-5617798 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	Not established
Body Width: 0.050 inches Body Height: 0.030 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Termination pad each end Test Data Document: 53711-5617798 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	Body Length:
0.050 inches Body Height: 0.030 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Termination pad each end Test Data Document: 53711-5617798 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	0.040 inches
Body Height: 0.030 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Termination pad each end Test Data Document: 53711-5617798 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	Body Width:
O.030 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Termination pad each end Test Data Document: 53711-5617798 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	0.050 inches
Power Dissipation Rating In Watts: 0.125 free air Style Designator: Termination pad each end Test Data Document: 53711-5617798 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	Body Height:
0.125 free air Style Designator: Termination pad each end Test Data Document: 53711-5617798 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	0.030 inches
Style Designator: Termination pad each end Test Data Document: 53711-5617798 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	Power Dissipation Rating In Watts:
Termination pad each end Test Data Document: 53711-5617798 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	0.125 free air
Test Data Document: 53711-5617798 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	Style Designator:
53711-5617798 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	Termination pad each end
excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	Test Data Document:
Shelf Life: N/a	53711-5617798 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
N/a	excludes any specification, standard or other document that may be referenced in a basic governing drawing)
	Shelf Life:
Unit Of Measure:	N/a
	Unit Of Measure:
Demilitarization:	Demilitarization:
No	No
Fiig:	Fiig:
A001a0	A001a0