Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-273-7254

## Section Quantity:

1

Body Style:

Rectangular bushing mounted

# Reliability Indicator:

Not established

### First Flat Length:

0.325 inches

#### Flat Height:

0.218 inches

Shaft Diameter:

0.250 inches

Shaft Length:

0.720 inches

#### Mounting Bushing Length:

## 0.375 inches

Body Length:

0.510 inches

## Body Width:

0.500 inches

#### Body Height:

0.500 inches

### Shaft Style:

Round, flatted

#### Actuator Type:

Single shaft

## Screw Thread Diameter:

0.375 inches

## Screw Thread Series Designator:

Unef

# Screw Thready Qty Per Inch (tpi):

32.0

## **Terminal Location:**

Lower adjacent side single row

## **Mounting Method:**

Standard bushing

# **Electrical Resistance Per Section:**

5.0 kilohms single section

# Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

# Power Dissipation Rating Per Section In Watts:

0.25 free air single section



#### **Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 single section

### Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

## Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

## Demilitarization:

No

### Fiig:

A002a0