## NSN 5905-01-274-1185

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-01-274-1185

Electrical Resistance: 5.110 ohms Resistance Tolerance in Percent: -1.000/-1.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature in Deg Celsius At Full Rated Power: 150.0 Ambient Tempurature in Deg Celsius At Even Percent Rated Power: 150.0 Ambient Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0/-150.0 Inclosure Method: Uninclosed Terminal Type: Ferrule Reliability Indicator: Not established Terminal Length: 0.040 inches Body Diameter: 0.079 inches Body Diameter: 0.251 inches Power Dissipation Rating in Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 25622-5188894 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Na Unit of Measure: Demilitarization: No Figig A001a0	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
5.110 ohms Resistance Tolerance in Percent: -1.000/41.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0/4150.0 Inclosure Method: Uninclosed Terminal Type: Ferrule Reliability Indicator: Not established Terminal Length: 0.040 inches Body Diameter: 0.079 inches Body Length: 0.251 inches Power Dissipation Rating in Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 2/622-5188894 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Na Unit Of Measure:	-100.0/+100.0
Resistance Tolerance In Percent: -1.000/-4.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Uninclosed Terminal Type: Ferrule Reliability Indicator: Not established Terminal Length: 0.040 inches Body Diameter: 0.079 inches Body Length: 0.251 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 2/E922-5188894 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheft Life: N/a Unit Of Measure:	Electrical Resistance:
-1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Uninclosed Terminal Type: Ferrule Reliability Indicator: Not established Terminal Length: 0.079 inches Body Diameter: 0.079 inches Body Length: 0.251 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 25(222-5188894 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheff Life: Na Unit Of Measure:	5.110 ohms
Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 155.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Uninclosed Terminal Type: Ferrule Reliability Indicator: Not established Terminal Length: 0.040 inches Body Diamete: 0.079 inches Body Diamete: 0.079 inches Body Length: 0.251 inches Power Dissipation Rating in Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 2 822-5188894 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheff Life: N/a Unit Of Measure:	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0/4150.0  Inclosure Method: Uninclosed  Terminal Type: Ferrule  Reliability Indicator: Not established  Terminal Length: 0.040 inches  Body Diameter: 0.079 inches  Body Diameter: 0.079 inches  Power Dissipation Rating In Watts: 1.000 free air  Style Designator: Axial terminal each end  Test Data Document: 2)@22-51 lassBay drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure:  — Demilitarization: No  Filg:	-1.000/+1.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Uninclosure Method: Uninclosure Method: Uninclosure Regiability Indicator: Not established  Terminal Type: Ferrule Reliability Indicator: Not established  Terminal Length: 0.040 inches  Body Diameter: 0.079 inches  Body Length: 0.0251 inches  Power Dissipation Rating In Watts: 1.000 free air  Style Designator: Axial terminal each end  Test Data Document: 2522-51 18894 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a  Unit Of Measure: Demilitarization: No Flig:	Ambient Tempurature In Deg Celsius At Full Rated Power:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Uninclosed Terminal Type: Ferrule Reliability Indicator: Not established Terminal Length: 0.040 inches Body Diameter: 0.079 inches Body Diameter: 0.251 inches Power Dissipation Rating In Watts: 1.000 fee air Style Designator: Axial terminal each end Test Data Document: 2j622-5188894 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	70.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Uninclosed Terminal Type: Ferrule Reliability Indicator: Not established Terminal Length: 0.040 inches Body Diameter: 0.079 inches Body Diameter: 0.079 inches Body Length: 0.251 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 2/622-5188894 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: No Unit Of Measure: Demilitarization: No Fiig:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
-55.0/+150.0 Inclosure Method: Uninclosed Terminal Type: Ferrule Reliability Indicator: Not established Terminal Length: 0.040 inches Body Diameter: 0.079 inches Body Length: 0.251 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 2)622-5188894 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	150.0
Inclosure Method: Uninclosed Terminal Type: Ferrule Reliability Indicator: Not established Terminal Length: 0.040 inches Body Diameter: 0.079 inches Body Length: 0.251 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 2j622-5188894 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Uninclosed Terminal Type: Ferrule Reliability Indicator: Not established Terminal Length: 0.040 inches Body Diameter: 0.079 inches Body Length: 0.251 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 2j622-5188894 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	-55.0/+150.0
Terminal Type: Ferrule  Reliability Indicator: Not established  Terminal Length: 0.040 inches  Body Diameter: 0.079 inches  Body Length: 0.251 inches  Power Dissipation Rating In Watts: 1.000 free air  Style Designator: Axial terminal each end  Test Data Document: 2)622-518894 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure: Demilitarization: No Fig:	Inclosure Method:
Ferrule  Reliability Indicator:  Not established  Terminal Length: 0.040 inches  Body Diameter: 0.079 inches  Body Length: 0.251 inches  Power Dissipation Rating In Watts: 1.000 free air  Style Designator: Axial terminal each end  Test Data Document: 2)622-5188894 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fig:	Uninclosed
Reliability Indicator: Not established  Terminal Length: 0.040 inches  Body Diameter: 0.079 inches  Body Length: 0.251 inches  Power Dissipation Rating In Watts: 1.000 free air  Style Designator: Axial terminal each end  Test Data Document: 2)622-5188894 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure: Demilitarization: No Fig:	Terminal Type:
Note stablished  Terminal Length:  0.040 inches  Body Diameter:  0.079 inches  Body Length:  0.251 inches  Power Dissipation Rating In Watts:  1.000 free air  Style Designator:  Axial terminal each end  Test Data Document:  2j622-5188894 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fig:	Ferrule
Terminal Length:  0.040 inches  Body Diameter:  0.079 inches  Body Length:  0.251 inches  Power Dissipation Rating In Watts:  1.000 free air  Style Designator:  Axial terminal each end  Test Data Document:  2j622-5188894 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fig:	Reliability Indicator:
Body Diameter:  0.079 inches  Body Length: 0.251 inches  Power Dissipation Rating In Watts: 1.000 free air  Style Designator: Axial terminal each end  Test Data Document: 2j622-5188894 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fig:	Not established
Body Diameter:  0.079 inches  Body Length: 0.251 inches  Power Dissipation Rating In Watts: 1.000 free air  Style Designator: Axial terminal each end  Test Data Document: 2j622-5188894 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure: Demilitarization: No  Fig:	Terminal Length:
0.079 inches  Body Length: 0.251 inches  Power Dissipation Rating In Watts: 1.000 free air  Style Designator: Axial terminal each end  Test Data Document: 2j622-5188894 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fiig:	0.040 inches
Body Length:  0.251 inches  Power Dissipation Rating In Watts:  1.000 free air  Style Designator:  Axial terminal each end  Test Data Document:  2j622-5188894 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Body Diameter:
O.251 inches  Power Dissipation Rating In Watts: 1.000 free air  Style Designator:  Axial terminal each end  Test Data Document: 2j622-5188894 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fiig:	0.079 inches
Power Dissipation Rating In Watts:  1.000 free air  Style Designator:  Axial terminal each end  Test Data Document:  2j622-5188894 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Body Length:
1.000 free air  Style Designator: Axial terminal each end  Test Data Document: 2j622-5188894 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fiig:	0.251 inches
Style Designator:  Axial terminal each end  Test Data Document:  2j622-5188894 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Power Dissipation Rating In Watts:
Axial terminal each end  Test Data Document:  2j622-5188894 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	1.000 free air
Test Data Document:  2j622-5188894 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fiig:	Style Designator:
2j622-5188894 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Axial terminal each end
excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Test Data Document:
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	2j622-5188894 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
N/a Unit Of Measure: Demilitarization: No Fiig:	excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	<del></del>
Fiig:	Demilitarization:
	No
A001a0	Fiig:
	A001a0