

View Online at <https://aerobasegroup.com/nsn/5905-01-276-0598>

Section Quantity:

2

Body Style:

Rectangular bushing mounted

Reliability Indicator:

Not established

Shaft Diameter:

Between 0.124 inches and 0.126 inches

Shaft Length:

0.375 inches

Mounting Bushing Length:

Between 0.374 inches and 0.376 inches

Body Length:

Between 0.921 inches and 1.015 inches

Body Width:

Between 0.609 inches and 0.641 inches

Body Height:

Between 0.609 inches and 0.641 inches

Shaft Style:

Round

Shaft Bearing Type:

Sleeve

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

260.0

Maximum Starting Torque:

3.00 inch-ounces

Maximum Running Torque:

3.00 inch-ounces

Maximum Stop Torque:

64.00 inch-ounces

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

Between 0.289 inches and 0.321 inches

Fragility Factor:

Moderately rugged

End Application:

6625-01-251-4775 communication monitor

Screw Thread Diameter:

0.250 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Lower adjacent side two rows

Mounting Method:

Standard bushing

Features Provided:

Humidity proof

Cubic Measure:

0.417 cubic inches

Electrical Resistance Per Section:

10.0 kilohms all sections

Rotary Actuator Travel In Angular Deg:

Between 295.0 and 305.0

Resistance Temperature Characteristic Range Per Section In Percent:

+0.0/+7.0 -55 degrees celsius all sections and +0.0/+3.5 -25 degrees celsius all sections and +0.0/+2.0 0 degrees celsius all sections and -2.5/+2.5 85 degrees celsius all sections and +0.0/+5.5 120 degrees celsius all sections

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 all sections

Power Dissipation Rating Per Section In Watts:

0.5 free air all sections

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 all sections

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 all sections

Standard Taper Curve Per Section:

C all sections

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0