NSN 5905-01-276-0600

Section Quantity:

Rectangular w/mounting holes

Body Style:

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-276-0600

Reliability Indicator:
Not established
Mounting Hole Diameter:
Between 0.083 inches and 0.103 inches
Shaft Diameter:
Between 0.065 inches and 0.095 inches
Shaft Length:
Between 0.025 inches and 0.045 inches
Body Length:
Between 0.490 inches and 0.510 inches
Body Width:
Between 0.177 inches and 0.197 inches
Body Height:
Between 0.490 inches and 0.510 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
9000.0
Maximum Starting Torque:
5.00 inch-ounces
Maximum Running Torque:
5.00 inch-ounces
Lateral Distance Between Mounting Hole Centers:
Between 0.513 inches and 0.526 inches
Mounting Facility Quantity:
2
Terminal Location:
Rear end
Mounting Method:
Unthreaded hole
Electrical Resistance Per Section:
100.0 ohms single section
Rotary Actuator Travel In Angular Deg:
9000.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section

NSN 5905-01-276-0600

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No