# NSN 5905-01-276-2185

Film Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-276-2185

## Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

-5.0/+5.0 first temp coefficient

## **Electrical Resistance:**

953.000 ohms

## **Resistance Tolerance In Percent:**

-0.010/+0.010

## Ambient Tempurature In Deg Celsius At Full Rated Power:

## 125.0

## Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

175.0

# Tempurature Range Of Tempurature Coefficient In Deg Celsius:

-55.0/+125.0 temp range of first temp coefficient

## Inclosure Method:

Encapsulated

**Terminal Type:** 

Wire lead

Mil-std-1276 Wire Lead Type Designator:

С

Reliability Indicator:

Established

### Reliability Failure Rate Level In Percent:

0.010

### **Terminal Length:**

Between 0.875 inches and 1.875 inches

### **Body Length:**

Between 0.290 inches and 0.320 inches

### Body Width:

Between 0.295 inches and 0.345 inches

### **Body Height:**

Between 0.095 inches and 0.120 inches

### Power Dissipation Rating In Watts:

0.300 free air

#### **End Application:**

Down stg sim

Cubic Measure (non-core):

0.013 cubic inches

#### Unpackaged Unit Weight:

1.0 grams

#### Style Designator:

Terminals one edge

#### **Test Data Document:**

81349-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# NSN 5905-01-276-2185

Film Fixed Resistor - Page 2 of 2



**Specification Data:** 

81349-mil-r-55182/9 government specification

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A001a0