NSN 5905-01-276-2217

Inductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-276-2217				
Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:				
-30.0/+30.0				
Electrical Resistance:				
143.000 ohms				
Resistance Tolerance In Percent:				
-1.000/+1.000				
Ambient Tempurature In Deg Celsius At Full Rated Power:				
25.0				
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:				
275.0				
Tempurature Range Of Tempurature Coefficient In Deg Celsius:				
-55.0/+275.0				
Inclosure Method:				
Encased				
Terminal Type:				
Tab, solder lug				
Reliability Indicator:				
Established				
Reliability Failure Rate Level In Percent:				
0.010				
Terminal Length:				
Between 0.204 inches and 0.328 inches				
Body Length:				
Between 0.538 inches and 0.662 inches				
Body Width:				
Between 0.272 inches and 0.396 inches				
Body Height:				
Between 0.289 inches and 0.351 inches				
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:				
Between 0.434 inches and 0.454 inches				
Power Dissipation Rating In Watts:				
3.000 free air				
Terminal Width:				
0.085 inches				
End Application:				
5810-01-271-7807				
Mounting Hole Size:				
Between 0.088 inches and 0.098 inches				
Cubic Measure (non-core):				
0.064 cubic inches				

3.0 grams

Unpackaged Unit Weight:

NSN 5905-01-276-2217

Inductive Wire Wound Fixed Resistor - Page 2 of 2



~ .			
Stvie	e Des	sıan	ator:

Axial terminal (s)

Test Data Document:

81349-mil-r-39009 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-r-39009/1 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A001a0