

View Online at <https://aerobasegroup.com/nsn/5905-01-277-0732>

Section Quantity:

2

Body Style:

Rectangular bushing mounted

Reliability Indicator:

Not established

First Flat Length:

0.250 inches

Flat Height:

Between 0.092 inches and 0.096 inches

Shaft Diameter:

Between 0.124 inches and 0.126 inches

Shaft Length:

0.625 inches

Mounting Bushing Length:

0.250 inches

Body Length:

Between 0.921 inches and 1.015 inches

Body Width:

0.625 inches

Body Height:

0.625 inches

Shaft Style:

Round, flatted

Shaft Bearing Type:

Sleeve

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

260.0

Fragility Factor:

Moderately rugged

Terminal Location:

Longitudinally positioned on the circumference

Mounting Method:

Terminal

Features Provided:

Humidity proof

Cubic Measure:

0.396 cubic inches

Electrical Resistance Per Section:

2.0 kilohms all sections

Rotary Actuator Travel In Angular Deg:

300.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 all sections

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0/+100.0 all sections

Power Dissipation Rating Per Section In Watts:

2.0 free air all sections

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 all sections

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

85.0 all sections

Standard Taper Curve Per Section:

A all sections

Terminal Type And Quantity:

4 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0