## NSN 5905-01-279-5170

Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-279-5170
Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
-300.0/+300.0
Electrical Resistance:
3.000 kilohms
Resistance Tolerance In Percent:
-5.000/+5.000
Ambient Tempurature In Deg Celsius At Full Rated Power:
70.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
125.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
-55.0/+125.0
Inclosure Method:
Encapsulated
Terminal Quantity:
8
Terminal Type:
Pin
Reliability Indicator:
Not established
Terminal Length:
Between 0.125 inches and 0.150 inches
Body Length:
Between 0.768 inches and 0.798 inches
Body Width:
Between 0.050 inches and 0.103 inches
Body Height:
Between 0.332 inches and 0.350 inches
Power Dissipation Rating In Watts:
1.400 total network
End Application:
7025-01-192-9981 multiplexer-power supply group
Identical Value Resistor Quantity:
7 each resistor
Unpackaged Unit Weight:
0.9 grams
Style Designator:
Single inline
Test Data Document:
81349-mil-r-83401 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification

format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Specification Data:**

81349-mil-r-83401/5 government specification

## NSN 5905-01-279-5170

Film Fixed Resistor Network - Page 2 of 2



Shelf Life:	She	lf	Life:
-------------	-----	----	-------

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A001a0