

View Online at <https://aerobasegroup.com/nsn/5905-01-279-6753>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Shaft Length:

0.500 inches

Mounting Bushing Length:

0.375 inches

Body Length:

0.970 inches

Shaft Style:

Round

Effective Electrical Rotation In Deg Angular Rotation:

358.0

Maximum Starting Torque:

1.70 inch-ounces

Maximum Running Torque:

1.30 inch-ounces

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

20.0 kilohms single section

Rotary Actuator Travel In Angular Deg:

360.0

Power Dissipation Rating Per Section In Watts:

7.0 free air single section

Tap Location Tolerance Per Section:

-1.0/+1.0 degrees angular rotation single section

Resistance Tolerance Per Section In Percent:

-3.0/+3.0 single section

Actuator Travel Control Feature:

Continuous motion

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

60.0 single section

Precious Material And Location:

Terminals gold

Precious Material:

Gold

Test Data Document:

81349-mil-r-12934 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0