Section Quantity:

Nonprecision Wire Wound Variable Resistor - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5905-01-282-2025



1 **Body Style:** Cylindrical **Reliability Indicator:** Not established **Terminal Length:** 0.300 inches **Body Diameter:** Between 0.490 inches and 0.510 inches **Body Length:** Between 0.225 inches and 0.245 inches Actuator Type: Flush drive with slot-hole Maximum Starting Torque: 7.50 inch-ounces Maximum Running Torque: 7.50 inch-ounces **Maximum Stop Torque:** 30.00 inch-ounces **Center To Center Distance Between Terminals:** 0.200 inches **Terminal Location:** Rear end **Mounting Method:** Terminal **Electrical Resistance Per Section:** 2.0 kilohms single section Center To Center Distance Between Center Terminal And Outside Terminal: 0.100 inches Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 150.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -50.0/+50.0 single section **Power Dissipation Rating Per Section In Watts:** 1.0 free air single section **Resistance Tolerance Per Section In Percent:** -5.0/+5.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Precious Material And Location:**

Terminal surfaces gold

NSN 5905-01-282-2025

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Precious Material:

Gold

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0