

View Online at <https://aerobasegroup.com/nsn/5905-01-282-7804>

**Temperature Coefficient Of Resistance In Ppm Per Deg Celsius:**

-50.0 to 50.0

**Electrical Resistance:**

16.900 ohms

**Resistance Tolerance In Percent:**

-0.100 to 0.100

**Ambient Temperature In Deg Celsius At Full Rated Power:**

125.0

**Ambient Temperature In Deg Celsius At Zero Percent Rated Power:**

175.0

**Temperature Range Of Temperature Coefficient In Deg Celsius:**

-55.0 to 175.0

**Inclosure Method:**

Encapsulated

**Terminal Type:**

Wire lead

**Mil-std-1276 Wire Lead Type Designator:**

C

**Reliability Indicator:**

Established

**Reliability Failure Rate Level In Percent:**

0.001

**Terminal Length:**

Between 0.984 inches and 1.516 inches

**Body Diameter:**

Between 0.050 inches and 0.080 inches

**Body Length:**

Between 0.130 inches and 0.170 inches

**Power Dissipation Rating In Watts:**

0.050 free air

**End Application:**

A-7 flir ppl

**Special Features:**

Nuclear hardness critical items

**Nuclear Hardness Critical Feature:**

Hardened

**Unpackaged Unit Weight:**

0.11 grams

**Style Designator:**

Axial terminal each end

**Test Data Document:**

81349-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:**

81349-mil-r-55182/7 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A001a0